

Adjustable DC Power Supply



DC Power Supply; HY-Series



DIMENSION: 230x180 x95mm.
WEIGHT: 2-4 KGS



DIMENSION: 291x158x136 mm.
WEIGHT: 3-6 KGS



DIMENSION: 365x265x164 mm.
WEIGHT: 9-13 KGS



DIMENSION: 365x265x164 mm.
WEIGHT: 9-13 KGS

MODEL	HY - 1503D	HY - 1803D
Input Voltage	110/220 VAC+/-10%	
Output Voltage	0 - 15 VDC	0 - 18 VDC
Output Current	0 - 3 ADC	
Source Effect	0.02%+1mV	
Load Effect	0.01%+5mV	
Ripple & Noise	<1mVRMS	

3-1/2 DIGIT LCD DISPLAY ACCURACY VOLTAGE +/-1% 2 DIGIT

3-1/2 DIGIT LCD DISPLAY ACCURACY CURRENT +/-1.5% 1 DIGIT

MODEL	HY - 3003D	HY - 3005D
Input Voltage	110/220 VAC+/-10%	
Output Voltage	0 - 30 VDC	
Output Current	0 - 3 ADC	0 - 5 ADC
Source Effect	0.02%+1mV	
Load Effect	0.01%+5mV	
Ripple & Noise	<1mVRMS	

3-1/2 DIGIT LCD DISPLAY ACCURACY VOLTAGE +/-1% 2 DIGIT

3-1/2 DIGIT LCD DISPLAY ACCURACY CURRENT +/-1.5% 1 DIGIT

MODEL	HY - 3003D - 2	HY - 3005D - 2
Input Voltage	110/220 VAC+/-10%	
Output Voltage	2 x 0 - 30 VDC	
Output Current	2 x 0 - 3 ADC	2 x 0 - 5 ADC
Source Effect	0.02%+1mV	
Load Effect	0.01%+5mV	
Ripple & Noise	<1mVRMS	

FOUR SET FOR LCD DISPLAY ACCURACY IS +/-2.5%

MODEL	HY - 3010E	HY - 3020E
Input Voltage	110/220 VAC+/-10%	
Output Voltage	0 - 30 VDC	
Output Current	0 - 10 ADC	0 - 20 ADC
Source Effect	0.02%+1mV	
Load Effect	0.01%+5mV	
Ripple & Noise	<1mVRMS	

3-1/2 DIGIT LCD DISPLAY ACCURACY VOLTAGE +/-1% 2 DIGIT

3-1/2 DIGIT LCD DISPLAY ACCURACY CURRENT +/-1.5% 1 DIGIT