

เครื่องจ่ายไฟฟ้าสำรอง UPS

Line Interactive UPS

Features:

- Microprocessor control guarantees high reliability
- Equipped with Boost and Buck AVR to stabilize input voltage
- Built in DC start function enables UPS to be started up without AC power supplied
- Smart RS-232 Communication Port with Free Download Software from the internet
- Auto restart while AC recovery
- Compact size & light weight
- Provides Modem/Phoneline Surge protection
- Provides Overload Protection
- USB Option



Specification:

Input & Output	
Phase	Single
Input Voltage Range	81-145VAC/ 140-290VAC
Input Frequency	50/60 Hz $\pm 5\%$
Power Factor	>0.95
Output Voltage Range	110/120 VAC or 220/230/240 VAC $\pm 5\%$
Output Frequency	50/60 Hz $\pm 1\%$
Waveform	Modified Sine Wave
Battery	
Type	Sealed Lead Acid, Maintenance Free
Charge Time	90% Capacity after 8 hours
General	
Communication Interface	RS232; SNMP (optional)
Power Factor	0.6
Protection	Discharge, Overcharge and Overload protection
AC Mode	Green LED lighting
Battery Mode	Yellow LED Flashing every 10 seconds
Fault	Red LED lighting
Typical	2 ms
Environment Temperature	0 ~ 40°C
Environment Humidity	10% ~ 90%